

LENERGIZEE MOBILE 11KW

DETAILED CARD



TECHNICAL PARAMETERS

Index:	424977
EAN:	5905963424977
Category type:	Wallbox AC
Charging power [kW]:	11
Number of phases:	1 or 3
Charging mode:	3
Rated current (A):	16
Charging cable cross-section [mm ²]:	5x2.5
Number of connectors:	1

CHARACTERISTICS

Lenergizee Mobile 11kW is a portable charger for electric cars. Equipped with a TYPE 2 plug and a 5m cable. Current adjustment in the range of 8A / 10A / 13A / 16A. Switching between 3-phase charging on a power connector (max. 11kW) or a Schuko plug (max. 3.6kW). Protection rating: IP65 (device), IP54 (vehicle plug), IP67 (CEE plug). Built-in protection against overheating, DC leakage current A+ <6mA, real-time insulation monitoring. Built-in 2.8-inch LCD screen. Intuitive user interface. Communication via WiFi/Bluetooth. Integration with the Tuya app possible.

APPLICATION

The Lenergizee Mobile charger has been designed for users who value freedom and mobility. It is a universal solution that works well both at home and on the go. Thanks to a dedicated mounting bracket, it can be easily attached to a wall in your garage or driveway, ensuring convenient charging of your vehicle in a fixed parking space.

At the same time, its compact design and dedicated case allow you to safely transport and carry the charger in your car. You can take it anywhere — on a business trip, on holiday or to work — always ensuring that you have access to charging for your electric vehicle.

An additional advantage of the set is the adapter from a three-phase socket to a single-phase Schuko socket, which increases the range of applications and allows you to charge your vehicle almost anywhere, regardless of the type of power source available. This saves time, gives you greater independence and full control over the charging process.

LENERGIZEE MOBILE 11KW

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	424977	Type of housing finish:	mat
EAN:	5905963424977	Dimensions (H/W/T/S) [mm]:	230/97/53
Category type:	Wallbox AC	Net weight [kg]:	2.500
Charging power [kW]:	11	Gross weight [kg]:	4.650
Number of phases:	1 or 3	Mounting version:	wall-mounted
Charging mode:	3	Maximum charging current: [A]:	16
Rated current (A):	16	Number on the palette [pcs]:	36
Charging cable cross-section [mm ²]:	5x2.5	The number of implement units:	1
Number of connectors:	1	AC voltage range [V]:	3 x 230
Wire type:	type 2	Electrical protection class:	I
Cable type:	simple	Mounting dimensions [mm]:	105
Frequency [Hz]:	50-60	Version:	MOBILE
EMC class:	B (residential, business areas, commercial)	Plug type:	type 2
Integrated Protective Devices:	protection against DC current leakage ≤ 6mA	Cable length [m]:	5.70
Integrated security:	protection against short circuit to ground. protection against the effects of interrupted communication between the car and the wallbox	Remarks:	Length of cable with 3-phase socket – 45 cm
Surge protection [kV]:	2	Dimensions of single box [mm]:	204/395/395
Ingress protection:	IP65	Charging power regulation:	do 11kW
Impact resistance:	IK10	Power consumption in standby [W]:	2
Working temperature [°C]:	from -35 to +45	Overvoltage category:	external protection required - TYPE II
Storage temperature [degrees C]:	-40, +55	Destiny:	inwards, outwards
Authorization:	web application	Accessories included:	Case, wall mount for charger, wall mount for cable, 230V adapter
Charging schedule:	yes	Compliance with standards:	LVD 2014/35/EU, 2014/30/EU, 2015/863/EU, 2014/53/EU, PN-EN IEC 61851-1: 2019-10, EN IEC 61851-1: 2019, PN-EN IEC 61851-21-2: 2021-09, EN IEC 61851-21-2: 2021, PN-EN IEC 61439-7:2020:10, EN IEC 61439-7:2020, PN-EN IEC 62196-1: 2023-07, EN IEC 62196-1: 2022, PN-EN IEC 62196-2: 2023-07, EN IEC 62196-2: 2022, PN-EN IEC 63000: 2019-01, EN IEC 63000: 2018
Management application:	yes	Warranty [years]:	2
Material of the body:	PC	CE certificate:	121/2025
Colour of the body:	black RAL9005 matt	Manual:	Download PDF

LENERGIZEE MOBILE 11KW

DETAILED CARD

TECHNICAL DETAILS



Prześciówka z gniazdka trójfazowego na jednofazowe typu Schuko



Uchwyt na przewód ładujący z gniazdem typu 2




Uchwyt ścienny na ładowarkę mobilną



Torba



Redukcja Prześciówka 32A na 16A 5P



Aplikacja mobilna

LENERGIZEE MOBILE 11KW


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
EV100136	Wall bracket for cable
EV100134	Wall mount portable charger
EV100141	Rigid case with logo. black, 390x270x90mm
EV100133	1-phase 230V Schuko-CEE 16A 50cm adapter



Wall bracket for cable (EV100136)



Wall mount portable charger (EV100134)



Rigid case with logo. black, 390x270x90mm (EV100141)



1-phase 230V Schuko-CEE 16A 50cm adapter (EV100133)

Card creation date: 16 October 2026
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 121/2025